

MARINE HANDSET

NHS-200

NHS-200 marine handset can be used for VHF and MF/HF radio equipment, and easy to connect and compatible.



- Power Supply: DC 15 V
- MIC Impedance: 600 Ω
- MIC Sensitivity: -36 dBm
- SPK Impedance: 150 Ω



THERMAL PRINTER

NPT-100

NPT-100 thermal printer adopts Seiko printer head with the features of high speed, high reliability, low noise, compact size and easy operation. NPT-100 can be used for NAVTEX receiver, Inmarsat-C and other marine electronic devices.



- Printing Method: Thermal dot line printing
- Printing Width: 80 mm, 640 dot / Dot per line
- Resolution: 8 dots /mm
- Printing Speed: High or low speed
- Printing Head Life: 100 million pulse or more (at 25°C and rated energy)
- Character Matrix : ASCII character: 16 dot wide×24 dot high, 2.00 (W)×3.00 (H) mm
- Interface: One serial RS232 port and one parallel port
- AC/DC Adaptor: Input: AC 100 V~240 V, 50/60 Hz, Output: DC 8 V±5%
- NPS-120 DC/DC Converter (optional): Input: DC 24 V, Output: DC 8 V
- Environmental Conditions: Operating 0°C~40°C, Storage -20°C~60°C
- Size: 66 (H)×180 (W)×210 (D) mm
- Weight: 0.5 kg